



SMALL BI-ENERGY ARTICULATED BOOM




Telescopic Upper Boom

Narrow chassis allows operation in confined spaces

Weight Under 3.5 Tonnes

Fully Proportional Hydraulic Controls

Superb manoeuvrability makes it ideal for a wide range of applications



TECHNICAL DATA

METRIC	IMPERIAL
12.2m	40ft Oin
10.2m	33ft 6in
4m	13ft 1in
6.1m	20ft 0in
1.9m	6ft 3in
4.1m x 1.5m	13ft 5in x 4ft 11in
1.1m x 0.65m	3ft 7in x 2ft 2in
3435kg	7573lb
200kg	441lb
	12.2m 10.2m 4m 6.1m 1.9m 4.1m x 1.5m 1.1m x 0.65m 3435kg

*Length and width shown are when stowed.

FEATURE HYBRID POWERED

3b IPAF **IPÀF** 3b Diesel and Battery power for flexibility

OUTDOOR RATED

NON MARKING TYRES

A range of extra's for 'Hire or Purchase' designed to give you the GTAdvantage™



STOP NUISANCE BORROWING INTO OPERATOR TRAINING FOR WITH GTA SECURE™ OPERATOR THIS ACCESS PLATFORM



STAY FULLY CHARGED WITH TRANSFORMERS AND LEADS please contact us and send us an email in 0 \mathbf{O}

For more information about GTAccess: