

SKYJACK SKYJACK SJ3219

ELECTRIC SCISSOR LIFT ALTERNATIVES:
J Genie GS1932, Dingli DL0708





90° steering (zero inside turning radius)


30% Gradeability

Solid rubber, non-marking tyres

28 mph wind rating (12.5 m/s)

Tilt alarm with drive & lift cut-out

Forklift pockets and tie down/lift lugs



	. ۱
. 5) i

TECHNICAL DATA

SIZE	METRIC	IMPERIAL
Reach height	7.79m	25ft 5in
Platform height	5.79m	18ft 9in
Stowed height*	1.75m	5ft 7in
Length x width	1.78m x 0.81m	5ft 8in x 2ft 6in
Platform size	1.63m x 0.66m	5ft 3in x 2ft 1 in
Extended size	2.54m x 0.66m	8ft 3in x 2ft 1in
Weight	1312kg	2892lb
Lift capacity	227kg	500lb

^{*}Stowed height shown is with the handrails folded.

FEATURE



ELECTRIC

OUTDOOR

NON MARKING

IPAF.

IPAF 3a

Requires IPAF category 3a

A range of extra's for 'Hire or Purchase' designed to give you the GTAdvantage™







REMOVE THE RISK WITH GTA













For more information about GTAccess:

please contact us and send us an email



