



NIFTYLIFT SD170 SELF DRIVE WORK PLATFORM


Highly effective Bi-Energy system increases flexibility and maximises utilisation in a wider range of environments

Fully proportional hydraulic controls for lift and drive

Hydraulic outriggers for levelling on uneven ground

Telescopic upper boom and platform rotation for greater accuracy when positioning the platform

Weight Saving Design



TECHNICAL DATA

SIZE	METRIC	IMPERIAL
Reach height	17.1m	56ft 1in
Platform height	15.1m	49ft 6in
Up and down	6.6m	21ft 8in
Horizontal reach	8.7m	28ft 7in
Stowed height	2.1m	6ft 11in
Length x width	5.6m x 1.6m	18ft 4in x 5ft 3in
Deployed Width	4.4m	14ft 5in
Platform size	1.1m x 0.65m	3ft 7in x 2ft 2in
Weight	2750kg	6063lb
Lift capacity	200kg	441lb

Stowed travel size is 5.6 x 1.6 m (18' 4" x 5' 3")

er for flevihil

FEATURE



ROUGH TERRAIN

1b IPAF IPÀF 1b

OUTDOOR RATED

00



A range of extra's for 'Hire or Purchase' designed to give you the GTAdvantage™

For more information about GTAccess: please contact us and send us an email



STOP NUISANCE BORROWING WITH GTA SECURE™ OPERATOR TRAINING FOR THIS ACCESS PLATFORM





FUEL REFUEL ON-SITE THE EASY BOX WAY WITH A FUEL BOX!

